

Technical Data Sheet

Revision Date: Apr. 1. 2024

NO. WHPU_0001

Name: 69057

Version: 3.0

WANSUPER® 69057 POLYOLEFIN ELASTOMER (POE) DESCRIPTION

- WANSUPER® 69057 is an ethylene-butene copolymer produced by solution polymerization using metallocene catalyst.
- WANSUPER® 69057 is a low density and high performance copolymer modifier to provide excellent flow characteristics and impact properties.
- Typical application is photovoltaic module encapsulant.

PROPERTIES

	Test method	Unit	Typical values
Physical			
Melt index (2.16kg/190°C)	ASTM D1238	g/10min	5.0
Density	ASTM D792	g/cm ³	0.875
Mechanical¹			
Tensile modulus (100% secant, 500mm/min)	ASTM D638	MPa	2.2
Tensile strength at break(500mm/min)	ASTM D638	MPa	5.0
Elongation at break(500mm/min)	ASTM D638	%	800
Flexural modulus (1% secant)	ASTM D790	MPa	10
Tear strength (Type C)	ASTM D624	KN/m	35
Hardness (Shore A, 1 sec)	ASTM D2240	—	70
Hardness (Shore D, 1 sec)	ASTM D2240	—	18
Thermal			
Melting temperature	Wanhua method	°C	59
DSC Glass transition temperature	Wanhua method	°C	-51

Electrical

Volume resistivity	IEC60093	$\Omega \cdot \text{cm}$	>1.0E+15
--------------------	----------	--------------------------	----------

¹Measurements are based on specimens cut from compression molded plates.

Version information:

Date of first issue: Nov. 13. 2023

For further information please contact us:

Address: Wanhua Chemical Group Co., Ltd.

No.59, Chongqin Street, YEDA, Yantai, 264006, China

Customer service: Tel: +86 (535) 3031576 Fax: +86 (535) 6857160

Web-site: <http://www.whchem.com>

The information provided here is for reference only. The specification will be provided in the quality certificate or in the contract. It is the user's responsibility to test the material and its suitability for a process. We have no control over what another party does with the material and we cannot take any responsibility for another party's action. Nor will we be responsible for any indirect damages while using our products. The user is welcome to contact our customer and technical service center with questions on our products.